



Material Safety Data Sheet

Version: 02

Revision Date: 14-7-2025

Section 1. Product Information and Company Identification			
Product name	Acetone		
Mol. formula	C3H6O CAS No. 67-64-1		
Mol.wt	58,08 g/mol		
manufacturer name	Pioneers for laboratory chemicals		
Brand name	Piochem		
Address	Area 540, Industrial Zone 6th October city Giza, Egypt.		
Website	www.piochem.com		
E-mail	info@piochem.com		
Phone number	0 12 05700001		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Eye irritation (Category 2), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

F Highly flammable R11
Xi Irritant R36
R66

R67

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram





R/D-SOP-001-F02	Page 1 of 9	Issue Date: 03/11/2024	Effective Date:03/12/2024	Review Date: 03/12/2027	Issue No. 01	l
-----------------	-------------	------------------------	---------------------------	-------------------------	--------------	---



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261 Avoid breathing vapours.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C3H6O Molecular weight : 58,08 g/mol CAS-No. : 67-64-1

EC-No. : 200-662-2 Index-No. : 606-001-00-8

Registration number : 01-2119471330-49-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component Classification Concentration

Acetone

CAS-No. 67-64-1 Flam. Liq. 2; Eye Irrit. 2; STOT <= 100 %

EC-No. 200-662-2 SE 3; H225, H319, H336,

Index-No. 606-001-00-8 EUH066

Registration number 01-2119471330-49-XXXX

Hazardous ingredients according to Directive 1999/45/EC

Component Classification Concentration

Acetone

CAS-No. 67-64-1 F, Xi, R11 - R3 - R66 - R67 <= 100 %

EC-No. 200-662-2 Index-No. 606-001-00-8

Registration number 01-2119471330-49-XXXX

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16



R/D-SOP-001-F02 | Page 2 of 9 | Issue Date: 03/11/2024 | Effective Date: 03/12/2024 | Review Date: 03/12/2027 | Issue No. 01





SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.







SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Skin contact	Long-term systemic effects	186mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	62mg/kg BW/d
Consumers	Skin contact	Long-term systemic effects	62mg/kg BW/d
Workers	Inhalation	Acute systemic effects Long-term systemic effects Long-term systemic effects	2420 mg/m3
Workers	Inhalation		1210 mg/m3
Consumers	Inhalation		200 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	33,3 mg/kg
Marine water	1,06 mg/l
Fresh water	10,6 mg/l
Marine sediment	3,04 mg/kg
Fresh water sediment	30,4 mg/kg
Onsite sewage treatment plant	100 mg/l

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).



R/D-SOP-001-F02 | Page 4 of 9 | Issue Date: 03/11/2024 | Effective Date: 03/12/2024 | Review Date: 03/12/2027 | Issue No. 01



Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Form: liquid, clear Colour: colourless
Odour	No data available
Odour Threshold	No data available
рН	No data available
Melting point/freezing point	Melting point/range: -94 °C
Initial boiling point and boiling range	56 °C at 1.013 hPa
Flash point	-16,99 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 13 %(V) Lower explosion limit: 2 %(V)
Vapour pressure	533,3 hPa at 39,5 °C 245,3 hPa at 20,0 °C
Vapour density	No data available
Relative density	0,790-0.793 g/mL at 25 °C
Water solubility	completely miscible
	Odour Odour Threshold pH Melting point/freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Vapour pressure Vapour density Relative density



R/D-SOP-001-F02 Page 5 of 9 Issue Date: 03/11/2024 Effective Date: 03/12/2024 Review Date: 03/12/2027 Issue No. 01



o) Partition coefficient: n- log Pow: -0,24

octanol/water

p) Auto-ignition 465,0 °C

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available

s) Explosive properties No data available

t) Oxidizing properties No data available

9.2 Other safety information

Surface tension 23,2 mN/m at 20,0 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5.800 mg/kg

Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. Behavioral:Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

LC50 Inhalation - Rat - 8 h - 50.100 mg/m3

Remarks: Drowsiness Dizziness Unconsciousness

LD50 Dermal - Guinea pig - 7.426 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation - 24 h



R/D-SOP-001-F02 Page 6 of 9 Issue Date: 03/11/2024 Effective Date: 03/12/2024 Review Date: 03/12/2027 Issue No. 01





Serious eye damage/eye irritation

Eves - Rabbit

Result: Eye irritation - 24 h

Respiratory or skin sensitisation

- Guinea pig

Result: Does not cause skin sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

LC50 - Oncorhynchus mykiss (rainbow trout) - 5.540 mg/l - 96 h Toxicity to fish

Toxicity to daphnia and

other aquatic invertebrates

LC50 - Daphnia magna (Water flea) - 8.800 mg/l - 48 h

Toxicity to algae Remarks: No data available



R/D-SOP-001-F02 Issue Date: 03/11/2024 | Effective Date: 03/12/2024 Review Date: 03/12/2027 Page 7 of 9 Issue No. 01



12.2 Persistence and degradability

Biodegradability Result: 91 % - Readily biodegradable

(OECD Test Guideline 301B)

12.3 Bioaccumulative potential

Does not bioaccumulate.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1090 IMDG: 1090 IATA: 1090

14.2 UN proper shipping name

ADR/RID: ACETONE IMDG: ACETONE IATA: Acetone

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available





SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 190 7/2006.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. Eye irritation

Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

Full text of R-phrases referred to under sections 2 and 3

F Highly flammable

Xi Irritant

R11 Highly flammable. R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.



R/D-SOP-001-F02 Page 9 of 9 Issue Date: 03/11/2024 Effective Date: 03/12/2024 Review Date: 03/12/2027 Issue No. 01